

Technical Requirements -- JAMMIN COOL 2009

P.A. System (depends on size of venue) for Example :

Electro Voice XLC line array 6hang per side - sub 3x 2x18" per side or
JBL vertec VT 4889 line array 6hang per side - sub 3x 2x18" per side or
L'acoustics Vdosc linearray 6hang per side - sub 3x SB218 per side

Frontfill 2x SX360a per side or 2x L'acoustics XT115 hiQ per side

F.O.H. Mixing desk + Outboard

Soundcraft MH 4 or 3 or 2 40/8/2
2x EQ Klark Teknik DN 370
1x CD Player + 1 CD Burner
4x efx 1 PCM 70,80 or 90, 2 SPX 990 or 900, 1 D2 delay
4x Gates Klark Teknik DN 514 or Dramer DS 201
8x Comp. DBX 166, Klark Teknik DN 504

MONITOR Mixing Desk + Outboard (smaller venues mind. 6way Mon. From F.O.H.)

Soundcraft SM 20 or MH 4 or MH 3 or MH 2

12 x Wedges 2way activ 15"1,4" L'acoustics XT115 HiQ
2x 3way activ Sidefills
1x Sublow f. Drumfill
10x 31B Eq's Klark Teknik DN 360
1x efx PCM or SPX
Intercom

MICROPHONES + D.I.s

1x EV Re20
5x shure SM 58
8x shure SM57
3x AT 4041 cond.
1x sennheiser 421
10x D.I. Radial
4x UHF shure beta 58

LIGHTS

1x Scancommander + MA 24/6
Backtruss 3x 6bar PAR 64 , 1x ACL, 4x MAC 550
Frontruss 3x 6bar PAR 64, 6x ETC , 2x MAC 550
Floor 6x MAC 550, 1x ACL + Hazer
1 Followspot + Operator
Intercom



Musical Director : Mr. Schulz +49 172 6118 115
Tec. Director : Mr. Spain +49 171 52 13 414

Backline Anforderung:

Keyboards:

E-Piano Roland RD 170 o. RD 600 o. RD 700 incl Sustainpedal



Korg Keyboard: pa1xpro incl. Sustainpedal



Keyboardständer Spider Pro für beide Keyboards 18860



Drumhocker K & M 14000



Guitar Amp:

Fender Twin Reverb



Bass Amp incl. Top
SWR

oder

Ampeg



Drumkit Yamaha, D&W oder Pearl incl. Drumhocker

